

ENDURA BRAID

Endura Braid is a line that provides optimal performance, strength, and durability. Featuring a specially engineered 12-strand Dyneema® coated core with a braided polyester cover, it protects against UV deterioration and wear. Endura Braid has good knot-tying ability and is very low stretch.



Available Colors



Applications

- Winch lines
- Towing lines
- Lifting lines
- Wire rope replacement

Technical Data

Ø Diameter		Circumference	Weight		Breaking Streng	h	
	inch		-	lbs./100'	Minimum lbs.	Average lbs.	
mm	inch	inch	g/m	105./100	i wiimininum us.	Average ibs.	
16	5/8	2	175.60	11.80	27,000	29,000	
18	3/4	21/4	235.10	15.80	34,000	40,000	
22	7/8	23/4	311.00	20.90	48,500	53,900	
24	1	3	403.20	27.10	58,000	70,000	
28	1 1/8	31/2	511.80	34.40	81,000	96,000	
30	1 1/4	33⁄4	626.50	39.44	85,000	100,000	
36	1 1/2	41/2	834.70	54.10	149,000	171,000	
48	2	6	1406.20	92.50	255,000	283,000	
60	21/2	71/2	2199.30	143.40	343,000	381,000	
72	3	9	3237.90	213.60	529,000	588,000	

Features

- 🖌 Lightweight
- ✓ Excellent strength to weight ratio
- ✓ Very low elastic elongation