

HOLDFAST

Holdfast was engineered with one key goal in mind: GRIP. This rope utilizes HMPE and Nylon fibers to deliver a lightweight, high-strength, floating line that will grip on H-bitts and capstans much better than traditional 100% HMPE lines. Holdfast is coated with TEUFELBERGER's proprietary abrasion resistant coating that is specially formulated to yield higher strength and more durable and water-resistant lines. Coatings are available in assorted colors.



Available Colors



Applications

- Barge line
- H-bitt working line
- Tug pendant
- Tug winch line
- Messenger line
- Capstan line
- Winch line
- Dry dock line
- General purpose working line

Features

- ✓ Floats
- ✓ High friction coefficient
- ✓ Excellent grip
- ✓ Lightweight
- ✓ Easy to handle and inspect



Technical Data

Ø Diameter		Circumference	Weight		Breaking Strength	
mm	inch	inch	g/m	lbs./100'	Minimum lbs.	Average lbs.
18	¾	2 ¼	14.8	219.6	35,010	38,900
22	⅞	2 ¾	18.1	268.5	44,730	49,700
24	1	3	21.6	321.7	55,800	62,000
28	1 ⅛	3 ½	30.9	460.2	69,750	77,500
30	1 ¼	3 ¾	33.8	503.5	79,020	87,800
32	1 ⅕	4	38.5	573.4	92,650	102,500
34	1 ⅜	4 ⅛	43.4	646.2	97,650	108,500
36	1 ½	4 ½	46.9	697.9	110,070	122,300
40	1 ⅝	5	58.8	875.4	131,400	146,000
44	1 ¾	5 ½	66.7	991.6	152,550	169,500
48	2	6	79.2	1,177.6	176,850	196,500
56	2 ¼	7	113.3	1,685.2	247,950	275,500
60	2 ½	7 ½	133.4	1,984.6	278,100	309,000
64	2 ⅝	8	160.9	2,394.3	352,800	362,000
72	3	9	210.8	3,136.9	417,600	464,000