

MEGA BRAID

Mega Braid has a unique 12-strand single braid construction that offers the perfect combination of good looks, superb handling characteristics, excellent strength and controlled elongation. Mega Braid is flexible, easy to handle, resists kinking, and is easy to coil or flake. Mega Braid has less rotation, is lighter and is easier to handle than double braids of the same diameter.



Available Colors







Applications

- Mooring lines
- Towing lines
- Mooring tails
- Working lines
- Lifting slings

Features

- ✓ Easy to splice
- ✓ Excellent shock/energy absorption
- ✓ Good abrasion resistance

Technical Data

Ø Diameter		Circumference	Weight		Breaking Strength		
mm	inch	inch	g/m	lbs./100'	Minimum lbs.	Average lbs.	
16	5/8	2	147.30	9.90	7,900	10,300	
18	3/4	21/4	208.30	14.00	12,200	13,400	
22	7/8	23/4	255.90	17.20	19,000	21,100	
25	1	3	383.90	25.80	21,300	24,900	
28	1 1/8	31/2	505.90	34.00	28,000	34,900	
30	1 1/4	33/4	535.60	36.00	34,000	41,000	
36	1 1/2	41/2	825.70	55.50	41,000	48,000	
41	15/8	5	892.70	60.00	46,750	55,000	
44	13/4	51/2	992.40	66.70	51,850	61,000	

^{*} The technical data above reflects white rope specifications only. Colored rope specifications may differ and are available upon request.