

NYLON DOUBLE BRAID

Nylon Double Braid has the most elastic double braid construction available. It has excellent energy absorption properties and minimal strength loss due to UV exposure. It conforms to military specification Mil-R-24050 B&C and with twice as much stretch as polyester, Nylon Double Braid is great for docking and mooring lines because of its ability to absorb energy.



Available Colors



Applications

- Dock lines
- Anchor lines
- Hand lines
- Pulling lines
- Slings
- Mooring tails
- Pendant lines
- Shock lines

Features

- ✓ Excellent shock/energy absorption
- ✓ Durable
- ✓ Marine finish available

Technical Data

Ø Diameter		Circumference	Weight		Breaking Strength	
mm	inch	inch	g/m	lbs./100'	Minimum lbs.	Average lbs.
12	½	1½	104.10	7.00	7,500	8,000
14	⅝	1¾	136.90	9.20	10,500	12,300
16	⅝	2	148.80	10.00	11,000	13,100
18	¾	2¼	223.20	15.00	18,900	20,500
22	⅞	2¾	287.10	19.30	22,000	24,750
24	1	3	367.50	24.70	29,200	32,750
28	1⅛	3½	513.30	34.50	35,000	43,700
30	1¼	3¾	610.00	41.00	54,000	60,250
33	1⅝	4	684.40	46.00	66,800	74,250
38	1½	4½	828.70	55.70	70,000	77,550
41	1⅝	5	1032.50	69.40	80,000	90,000
44	1¾	5½	1202.10	80.80	96,150	102,000
51	2	6	1495.20	100.50	117,000	131,000
57	2¼	7	1978.80	133.00	150,000	166,600
63	2½	7½	2231.70	150.00	164,600	183,000
66	2⅝	8	2395.40	161.00	176,400	196,000
70	2⅞	9	3035.10	204.00	185,100	205,750
76	3	9	3392.20	228.00	225,000	261,000
83	3¼	10	4165.80	280.00	271,400	301,600

* The technical data above reflects white rope specifications only. Colored rope specifications may differ and are available upon request.