

VIEW A-A

MAX 300
MIN 280

PIN \varnothing 287

MAX 490

466

ELEVATION

736

HOLE \varnothing 292

SCREW M30
STAINLESS STEEL A4-80
TIGHTENING TORQUE 1350 Nm

FORK SOCKET Kg. 1499

NOTES:

DIMENSIONS: ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE INDICATED

ANGLES IN DEGREES (0 – 360)

MIN. SMOOTH 1 mm IF NOT DIFFERENTLY INDICATED

GENERAL DIMENSIONS ARE WITHOUT CORROSION PROTECTION

THE DIMENSION OF THE STEEL PLATE INCLUDES THE CORROSION PROTECTION

DIMENSIONS SUBJECT TO TECHNICAL MODIFICATIONS

TOLERANCES: ALL DIMENSIONS INDICATED IN THE DRAWING, UNLESS OTHERWISE INDICATED, ARE IN COMPLIANCE WITH THE FOLLOWING NORMS:

TOLERANCES FOR CASTINGS FOLLOW THE GRADE CT 11 AS PER ISO 8062-3

TOLERANCES FOR MACHINING FOLLOW THE GRADE M AS PER EN 22768-1

THESE SPECIFIED TOLERANCES REFER ONLY TO THE DIMENSIONS QUOTED IN

THE DRAWING

THE TOLERANCES FOR DIMENSIONS NOT INDICATED IN THE DRAWING CAN BE

REQUESTED IF NECESSARY



1	STANDARD	SELLA	CROTTI	LOMBARDINI	01.02.2021				
0	FOR COSTRUCTION	GANI	LOMBARDINI	AMBROSET	25.01.2016				
REV.	DESCRIPTION		DRAWN	CHECKED	APPROVED	DATE			

CLIENT:		TITLE:							
-		FORK SOCKET TTF-144							
JOB:		-							
-		ARRANGEMENT							
		DESIGNED	DRAWN	CHECKED	APPROVED				

		PRETE	SELLA	CROTTI	LOMBARDINI				
DWG SIZE	SCALE	DATE	JOB N°		DRAWING N°		REV.		
A2	1 : 5	01.02.2021	-	T	F	1	4	4	-
				-	-	-	-	2	2
				0	2	0	2	2	1