


RIGGING ROPES

Splicing instructions

Together in Motion

SIRIUS / STA SET / POLY NYLON




Tie a knot about 4 m from the rope end to prevent rope from moving.


Mark A, B, C. Measures according to table below.




Mark D in a distance of 8 braids from A.





From D towards the rope end mark every fifth pair of yarns. Later on these marks are needed for cutting off the yarns for even tapering.




Pull out the core at B and mark the point of exit 1.
















Pull the cover end (behind D) through the core from 2 to 3.



Pull the section 2 to 3 towards D as tightly as possible. Pull out the yarns marked before and cut them off for even tapering. Taper the remaining yarns at the tip.



Bring section 2 to 3 back into position. D and 2 must be in the same place. Fix with two to three stitches using e.g. whipping twine of 0,5mm.



Even out cover and core. At mark C, where the core exits the cover, add a marking on the core. Pull the core out further, make a straight cut, unravel the rope end for 6 cm and taper the tip along those 6 cm.

Pull hard to get the cover in place. .






In the finished splice marks A and B are in the same place.




Add a lock stitch by hand to make sure that the splice may not slip apart. See below for lock stitch.

	Markings in [cm]					
	Cover			Core		
	From end	AB	BC	From 1 to 2	From 2 to 3	
	to A					
Sirius 12 mm	26	77	9	12	26	
Sirius 14 mm	30	78	10	13	30	
Sirius 16 mm	34	79	12	15	34	
Sirius 18 mm	38	80	13	16	38	
Sirius 20 mm	42	81	14	17	42	
Sta-Set 1/2" / 12,7 mm	26	77	9	12	26	
Sta-Set 9/16" / 14,3 mm	30	78	10	13	30	
Sta-Set 5/8" / 15,9 mm	30	78	10	13	30	
Sta-Set 3/4" / 19, 1mm	40	81	14	17	40	
Sta-Set 7/8" / 22,2 mm	46	83	16	19	46	
Sta-Set 1" / 25,4 mm	53	85	18	21	53	
PolyNylon 1/2" / 12,7 mm	28	77	10	13	28	
PolyNylon 9/16" / 14,3 mm	34	78	12	15	34	
PolyNylon 5/8" / 15,9 mm	34	79	12	15	34	
PolyNylon 3/4" / 19,1 mm	42	81	14	17	42	
PolyNylon 7/8" / 22,2 mm	47	83	16	19	47	
PolyNylon 1" / 25,4 mm	55	85	18	21	55	


TREX



Mark A, B, C. 1 is the rope end near A. 2 is the other rope end. Measures according to table below. The distance between A and B defines the eye size.



Pull the rope end 1 through the rope at B until A meets B.



Pull rope end 2 through the rope just underneath the point where A and B meet.

See next picture for more details.





Pull tight and even out the rope at A/B.

Introduce rope end 1 into the rope just underneath A/B and exit again at C.



Pull out as much of rope end 1 as possible and fix with a needle near C. Remove 8 rope strands at equal distances and taper the rope end.



Remove the needle, even out the rope.



Add a lock stitch by hand to make sure that the splice may not slip apart.


See below for lock stitch.

Distances of marks	1 to A	AB (for a 35 cm eye)	BC
tRex 3/8" (9,5 mm)	33 cm	73 cm	44 cm
tRex 7/16″ (11,1 mm)	35 cm	75 cm	46 cm
tRex 1/2" (12,7 mm)	40 cm	77 cm	52 cm
tRex 5/8″ (15,9 mm)	51 cm	78 cm	76 cm
tRex 3/4" (19,1 mm)	61 cm	80 cm	80 cm
tRex 7/8″ (22,2 mm)	71 cm	82 cm	94 cm

ARBORWINCH LINE




Tie a knot about 4 m from the rope end to prevent rope from moving.




Cut rope end with a hot knife and mark A, B and C

A.....25 cm from end AB.....10 cm BC.....76 cm (for a 35 cm eye)




Cut off cover at A.




Pull out core and fix with a needle about 1,85 m from the rope end.


Mark 1 on the core (including intermediate cover) at 179 cm from the rope end.




Cut intermediate cover at 1, remove the intermediate cover (from 1 to the rope end) and fix the cut end with adhesive tape.




Mark 2 on the core at 37 cm from the rope end.




Pull cover back as far as mark 2. Unravel cover as far as 1,5 cm before mark B.




Taper the cover: Cut off half the yarns at 1,5 cm before B, cut another quarter of the yarns halfway and taper the remaining yarns until the end.




Wind adhesive tape around tapered cover from marks B to 2. Pull cover back in place and fix at mark C with a needle.




Just behind the needle at C pull out the cover until mark 1 appears. Then fix with another needle.




Insert the core end (behind mark 2) into the core next to mark C until mark 1.



Pull core end out at mark 1 and taper along 30 cm: Remove 4 braids at equal distances, cut them off and taper the remaining rope end.



Pull tapered core back (and even




Pull core into cover. Mark B must disappear inside the cover. It is recommended to use a winch to pull really hard.

Add a lock stitch by hand to make sure that the splice may not slip

See next page for the lock stitch.


apart.






В

LOCK STITCH




Step 1

Pass stitching through spliced area near throat of eye as shown.



Step 2 Reinsert as shown pulling snug but not tight.



Step 3

Continue to reinsert as shown until you have at least 3 complete stitches.

Step 4

Rotate spliced part of rope by 90° and reinsert end A into spliced area in the same way as in Steps 1, 2 and 3. The splice will now be stitched in two planes perpendicular to each other. Make sure you do not pull the stitching too tight.

Step 5

After stitching at least three complete stitches as in Step 3, extract both ends A and B together through the same opening in the braid. Tie them together with a square knot and reinsert back into braid. For double braids, reinsert the knot between the cover and core.

NOTES



Download Treecare Catalogue



TEUFELBERGER Fiber Rope GmbH

Vogelweiderstraße 50 4600 Wels, Austria Telephone: +43 (0) 7242 413-0 Fax: +43 (0) 7242 413-169 fiberrope@teufelberger.com

www.teufelberger.com

